

11AC 1750M High Power Ceiling Access Point W185AP (TH)



Specification

Hardware Features	
AP Type	Fat AP
Chipset	BCM4708
CPU Frequency	1 GHz
Flash	8 M
RAM	64 M
Interfaces	2*GE LAN
Antennas	2.4G 3*5dbi antennas 5G 2*5dbi antennas
Button	1*Reset
Power Method	PoE 802.3at
Maximum Power Consumption	24W
Maximum Transmit Power	2.4 GHz 15 dBm* 5 GHz 25 dBm*
LED indicator	SYS, 2.4G WiFi, 5G WiFi
Software Features	
Kernel	Linux

Compliant Standards	IEEE 802.11ac/n/g/a/b
Frequency Range	2.4 G & 5G
Maximun wireless speed	2.4 G 450 Mbps 5G 1350 Mbps
Wireless Basic Settings	8 SSID at 2.4 G Radio 4 SSID at 5G Radio Enable/Disable Wireless Radio Wireless Client isolation Wireless Access Control Wireless Client list Adjustable transmit power QVLAN
Wireless Security Settings	64/128 WEP WPA-PSK WPA2-PSK WPA & WPA2-PSK WPA WPA2
Working mode	AP,Repeater,Universal Repeater
Maximum Concurrent Clients	2.4 G 30 Clients 5G 30 Clients
Modulation	MIMO-OFDM/OFDM/DSSS
LAN Settings	Static IP/Dynamic IP
VPN Pass - Through	PPTP/L2TP
Management Tool	SNMP (v1& v2c) Reboot System Log Firmware update Time & Date Setting Backup/Restore Configuration Username Management Diagnostic Tool(ping&Traceroute)
Other	
Package Contents	11AC 1750M High Power Ceiling Acess Point 2*Mounting Bracket 1* Quick Installation Guide 2* Ethernet cable 1* PoE Injector 1* Power Adapter 5* Screws 5* Plastic anchor bolt
Operating Temperature	-10°C ~ 45°C
Storage Temperature	-30°C ~ 70°C
Operating Humidity	10% ~ 90% non-condersing
Storage Humidity	10% ~ 90% non-condersing
Default Settings	IP Adress: 192.168.0.254 Login Username: admin Login Username: admin
Certifications	FCC/CE/Rohs