

300M Wireless Ceiling Access Point

W40AP (TH)



Specification

Hardware Features	
Dimensions	144.2*144.2*40.12mm
AP Type	Fat AP
Interfaces	1*FE LAN
Antennas	2dbi printed antennas
Button	1*Reset
Power Method	802 3af PoE/DC 12V=1A
Maximum Power Consumption	8W
Maximum Transmit Power	18dbm*
LED indicator	SYS
Software Features	
Compliant Standards	IEEE 802.11n/g/b
Frequency Range	2.4GHz
Maximum wireless speed	300Mbps

*For Thailand country

Wireless Basic Settings	4 SSID Enable/Disable Wireless Radio Wireless Client isolation Wireless Access Control Wireless Client list
Wireless Security Settings	64/128 WEP WPA-PSK WPA2-PSK WPA & WPA2-PSK WPA WPA2
Working mode	AP, WDS, Universal Repeater
Maximum Concurrent Clients	15
Receiver sensitivity	b mode : 1M -89dBm@8% 11M -87dBm@8%PER ; g mode : 54M -74dBm@8%PER ; n mode : 72.2M -72dBm@8%PER ; 150M -70dBm@8%PER
Modulation	MIMO-OFDM/OFDM/DSSS
LAN Settings	Static IP Dynamic IP
DHCP Server	DHCP Server Clients list
VPN Pass-Through	PPTP L2TP
Management Tool	SNMP(v1&v2c) Reboot System Log Firmware update Time & Date Setting Backup/Restore Configuration Username Management Diagnostic Tool(ping)
Others	
Package Contents	Wireless N300 Ceiling Access Point W40AP 1*Mounting Bracket 1*Quick Installation Guide 1*Ethernet cable 1*Resource CD 1*Power Adapter 4*Screws 4*Plastic Bolt
Operating Temperature	-10°C~45°C
Storage Temperature	-30°C~70°C
Operating Humidity	10%~90% non-condensing
Storage Humidity	10%~90% non-condensing
Default Settings	IP Address: 192.168.0.254 Login Username: admin Login Password: admin
Certifications	FCC/CE/Rohs